

---

# Contents

---

|   |            |
|---|------------|
| <b>Preface</b>  | <b>xv</b>  |
| <b>Editors Biographies</b>  | <b>xix</b> |
| <br>  |            |
| <b>Part I Nanocomposites: Structure and Properties</b>                          | <b>1</b>   |
| <br>  |            |
| <b>Chapter 1 Carbon Nanotube-Reinforced Polymers: a State of the Art Review</b> | <b>3</b>   |
| 1 Introduction  | 3          |
| 2 General Problems in Nanocomposite Technology                                  | 4          |
| 3 Experimental  | 6          |
| 3.1 Manufacturing of Multiple-Wall Carbon Nanotubes                             | 6          |
| 3.2 Treatment of Carbon Nanotubes   | 7          |
| 3.3 Matrix Polymers   | 7          |
| 3.4 Electron Microscopy   | 7          |
| 3.5 Dynamic-Mechanical Thermal Analysis   | 8          |
| 4 Results   | 8          |
| 4.1 Comparison of the Multiple-Wall Carbon Nanotubes Studied                    | 8          |
| 4.2 Purification  | 10         |
| 4.3 CNT/Epoxy Composites: Dispersion, Matrix Bonding, and Functionalization     | 11         |
| 4.3.1 Dispersion  | 11         |
| 4.3.2 Nanotube-Matrix Interaction   | 13         |
| 4.3.3 Functionalization   | 13         |
| 4.4 Microscopy  | 15         |
| 4.4.1 Matrix Bonding to the Nanotubes   | 15         |
| 4.4.2 Crack Bridging and Telescopic Pull-Outs                                   | 16         |
| 4.5 Thermal and Mechanical Properties   | 17         |
| 4.6 Electrical Properties   | 18         |
| 5 Conclusions   | 21         |
| 6 Acknowledgements  | 21         |
| 7 References  | 22         |

|                  |   |           |
|------------------|---|-----------|
| <b>Chapter 2</b> | <b>Application of Non-Layered Nanoparticles in Polymer Modification</b>   | <b>25</b> |
| 1                | Introduction  | 25        |
| 2                | Surface Treatment and Compounding   | 27        |
| 2.1              | Raw Materials   | 27        |
| 2.2              | Pregrafting of the Nanoparticles by Irradiation   | 27        |
| 2.3              | Characterization of the Irradiation Products  | 28        |
| 2.4              | Preparation of PP-Based Nanocomposites and Their Characterization   | 28        |
| 2.5              | Preparation of Epoxy-Based Nanocomposites and Their Characterization  | 29        |
| 3                | Thermoplastic Systems   | 29        |
| 3.1              | Effect of Irradiation Grafting Polymerization on the Nanoparticles  | 29        |
| 3.2              | Tensile Properties  | 30        |
| 3.3              | Fractography  | 35        |
| 4                | Thermosetting Systems   | 36        |
| 4.1              | Interfacial Interactions in the Composites  | 36        |
| 4.2              | Curing Behavior   | 38        |
| 4.3              | Friction and Wear Performance   | 38        |
| 5                | Conclusions   | 42        |
| 6                | Acknowledgements  | 43        |
| 7                | References  | 43        |
| <b>Chapter 3</b> | <b>Reinforcement of Thermosetting Polymers by the Incorporation of Micro- and Nanoparticles</b>                           | <b>45</b> |
| 1                | Introduction  | 45        |
| 2                | Manufacturing of Thermosetting Nanocomposites   | 47        |
| 3                | Properties of Nanocomposites  | 50        |
| 3.1              | Stress-Strain Behavior  | 50        |
| 3.2              | Impact Behavior   | 54        |
| 3.3              | Stiffness-Impact Energy Relationship  | 55        |
| 3.4              | Dynamic Mechanical Properties   | 56        |
| 3.5              | Wear Performance  | 57        |
| 4                | Acknowledgements  | 60        |
| 5                | References  | 60        |
| <b>Chapter 4</b> | <b>Polyimides Reinforced by a Sol-Gel Derived Organosilicon Nanophase: Synthesis and Structure-Property Relationships</b> | <b>63</b> |
| 1                | Nanocomposites Based on Flexible-Chain Polymers   | 63        |
| 2                | Nanocomposites Based on Semi-Rigid Chain Polymers (Polyimides)  | 66        |

|     |   |    |
|-----|---|----|
| 2.1 | <i>In Situ</i> Generation of an Organosilicon Nanophase | 67 |
| 2.2 | Structural Characterization                             | 68 |
| 2.3 | Water Uptake  | 69 |
| 2.4 | Thermomechanical Performance                            | 70 |
| 2.5 | Dielectric Properties                                   | 72 |
| 3   | Conclusions   | 73 |
| 4   | Acknowledgements  | 74 |
| 5   | References  | 74 |

|                  |   |           |
|------------------|---|-----------|
| <b>Chapter 5</b> | <b>Layered Silicate/Rubber Nanocomposites<br/>via Latex and Solution Intercalations</b> | <b>77</b> |
| 1                | Concept of Nanoreinforcement  | 77        |
| 2                | Production of Rubber/Clay Nanocomposites  | 78        |
| 2.1              | Latex Intercalation   | 79        |
| 2.1.1            | Nanocomposites from Rubber Latex  | 79        |
| 2.1.2            | Nanocomposites from Latex Blends  | 81        |
| 2.1.3            | Radiation-Vulcanized NR Latex   | 84        |
| 2.2              | Solvent-Assisted Intercalation  | 87        |
| 3                | Future Issues   | 88        |
| 4                | Acknowledgements  | 88        |
| 5                | References  | 89        |

|                  |   |           |
|------------------|---|-----------|
| <b>Chapter 6</b> | <b>Property Improvements of an Epoxy Resin<br/>by Nanosilica Particle Reinforcement</b> | <b>91</b> |
| 1                | Introduction and State of the Art   | 91        |
| 2                | Preparation and Characterization Techniques   | 94        |
| 2.1              | Basic Material Components   | 94        |
| 2.2              | Preparation of Nanosilica-Filled Epoxy Composites                                       | 94        |
| 2.3              | Structural and Mechanical Analysis  | 95        |
| 2.3.1            | Microstructure  | 95        |
| 2.3.2            | Viscosity Studies of the Unfilled<br>and Filled Resin                                   | 95        |
| 2.3.3            | Mechanical Properties   | 95        |
| 2.3.4            | Tribological Properties   | 96        |
| 2.3.5            | Failure Analysis  | 96        |
| 3                | Microstructural and Rheological Details   | 96        |
| 3.1              | Particle Distribution   | 96        |
| 3.2              | Viscosity   | 98        |
| 4                | Mechanical Properties   | 99        |
| 4.1              | Three-Point Bending   | 99        |
| 4.2              | Microhardness   | 99        |
| 4.3              | Fracture Toughness  | 101       |
| 4.4              | Tribological Properties   | 101       |
| 5                | Conclusions   | 103       |

|                  |   |            |
|------------------|---|------------|
| 6                | Acknowledgements  | 104        |
| 7                | References  | 104        |
| <b>Part II</b>   | <b>Special Characterization Methods and Modeling</b>  | <b>107</b> |
| <b>Chapter 7</b> | <b>Micro-Scratch Testing and Finite Element Simulation of Wear Mechanisms of Polymer Composites</b>         | <b>109</b> |
| 1                | Introduction  | 109        |
| 2                | Micro-Scratch Testing   | 110        |
| 3                | The Representative Wear Mechanisms  | 113        |
| 4                | Wear Considerations by Finite Element Contact Analysis  | 114        |
| 4.1              | Finite Element Macro/Micro-Contact Models   | 115        |
| 4.2              | Normal Fiber Orientation  | 116        |
| 4.3              | Parallel Fiber Orientation  | 118        |
| 4.4              | Anti-Parallel Fiber Orientation   | 120        |
| 5                | Finite Element Simulation of the Fiber/Matrix Debonding   | 121        |
| 5.1              | Debonding Model and Interface Elements  | 122        |
| 5.1.1            | Interface Elements  | 122        |
| 5.1.2            | Conditions of Debonding   | 123        |
| 5.1.3            | Unloading Considerations  | 125        |
| 5.1.4            | The Debonding Algorithm   | 125        |
| 5.2              | Calculations for N-Oriented Carbon Fibers in a PEEK Matrix  | 126        |
| 6                | Conclusions   | 129        |
| 7                | Acknowledgements  | 130        |
| 8                | References  | 130        |
| <b>Chapter 8</b> | <b>Determination of the Interface Strength of Polymer-Polymer Joints by a Curved Interface Tensile Test</b> | <b>133</b> |
| 1                | Introduction  | 133        |
| 2                | Curved Interface Tensile Test   | 136        |
| 3                | Stress Calculation by Finite-Element Analysis   | 137        |
| 3.1              | Flat Interface  | 138        |
| 3.2              | Curved Interface  | 138        |
| 4                | Experimental Observations   | 140        |
| 4.1              | Materials and Specimen Preparation  | 140        |
| 4.2              | Tensile Tests and Strain Estimation   | 142        |
| 4.3              | Determination of the Adhesion Strength  | 144        |
| 5                | Conclusions and Outlook   | 145        |
| 6                | References  | 146        |

|                   |   |            |
|-------------------|---|------------|
| <b>Chapter 9</b>  | <b>Manufacturing and Characterization of Microfibrillar Reinforced Composites from Polymer Blends</b> | <b>149</b> |
| 1                 | Introduction  | 149        |
| 2                 | Materials, Processing, and Characterization Techniques  | 151        |
| 3                 | Structure and Properties of MFCs  | 153        |
| 3.1               | Structure and Properties of MFCs Based on PET/PP Blends   | 153        |
| 3.1.1             | Morphology  | 153        |
| 3.1.2             | Mechanical Properties of the Drawn Blends After Processing  | 157        |
| 3.2               | Structure and Properties of MFCs Based on LCP/PPE Blends  | 159        |
| 3.2.1             | Morphology  | 159        |
| 3.2.2             | Mechanical Properties of Injection Molded LCP/PPE Blends with MFC Structure                           | 162        |
| 4                 | Conclusions   | 164        |
| 5                 | Acknowledgements  | 165        |
| 6                 | References  | 165        |
| <b>Chapter 10</b> | <b>Tribological Characteristics of Micro- and Nanoparticle Filled Polymer Composites</b>              | <b>169</b> |
| 1                 | Introduction  | 169        |
| 2                 | Influence of Particle Size: from Micro- to Nanometer  | 170        |
| 3                 | Influence of the Nanoparticle Volume Content  | 171        |
| 4                 | Particle-Filled Polytetrafluoroethylene   | 174        |
| 5                 | Integration of Inorganic Particles With Traditional Fillers   | 175        |
| 5.1               | Inorganic Particles and Other Fillers   | 175        |
| 5.2               | Combinative Effect of Nanoparticles and Short Carbon Fibers   | 175        |
| 6                 | Conclusion  | 182        |
| 7                 | Acknowledgement   | 182        |
| 8                 | References  | 182        |
| <b>Part III</b>   | <b>Macrocomposites: Processing and Application</b>  | <b>187</b> |

|                   |  |            |
|-------------------|--|------------|
| <b>Chapter 11</b> | <b>Production of Thermoplastic Towpregs and Towpreg-Based Composites</b> | <b>189</b> |
| 1                 | Introduction   | 189        |
| 2                 | Raw Materials  | 190        |
| 3                 | Production of Towpregs   | 190        |
| 3.1               | Process and Equipment Description  | 190        |

|  |     |
|--|-----|
| 3.2 Relationships Between Final Properties and Processing Conditions           | 192 |
| 3.2.1 Parameters Affecting the Polymer Powder Deposition                       | 192 |
| 3.2.2 Influence of the Processing Conditions on the Final Composite Properties | 193 |
| 4 Production of Towpreg-Based Composites                                       | 194 |
| 4.1 Compression Molding  | 194 |
| 4.1.1 Process Description  | 194 |
| 4.1.2 Molding Conditions   | 194 |
| 4.2 Process Modeling   | 195 |
| 4.2.1 Isothermal Consolidation   | 196 |
| 4.2.2 Non-Isothermal Consolidation   | 197 |
| 4.2.3 Validation of the Consolidation Model                                    | 198 |
| 4.3 Pultrusion   | 200 |
| 4.3.1 Process Description  | 200 |
| 4.3.2 Processing Conditions  | 201 |
| 4.3.3 Process Modeling   | 201 |
| 4.4 Filament Winding   | 203 |
| 4.4.1 Process Description  | 203 |
| 4.4.2 Processing Conditions  | 203 |
| 4.4.3 Relationships Between Final Properties and Processing Conditions         | 204 |
| 4.5 Long Fiber-Reinforced Composite Stamping                                   | 206 |
| 4.5.1 Process Description  | 206 |
| 4.5.2 Processing Conditions  | 206 |
| 5 Composite Properties   | 206 |
| 5.1 Mechanical Properties of Continuous Fiber-Reinforced Composites            | 207 |
| 5.2 Mechanical Properties of Discontinuous Fiber-Reinforced Composites         | 207 |
| 6 Conclusions  | 211 |
| 7 Acknowledgements   | 211 |
| 8 References   | 212 |

|  |            |
|--|------------|
| <b>Chapter 12 Manufacturing of Tailored Reinforcement for Liquid Composite Molding Processes</b> | <b>215</b> |
| 1 Introduction   | 215        |
| 2 Pre-selection of Sewing Thread   | 217        |
| 2.1 Selection Criteria   | 217        |
| 2.2 Polyester Thread in Global Preform Sewing  | 219        |
| 3 Tailored Reinforcements  | 220        |
| 4 Stitching Parameters and Their Influence on the Fiber-Reinforced Polymer Composites            | 221        |

|       |  |     |
|-------|--|-----|
| 4.1   | Machine Parameters   | 221 |
| 4.1.1 | Thread Tension   | 221 |
| 4.1.2 | Presser Foot Pressure                                      | 223 |
| 4.2   | Stitching Pattern  | 224 |
| 5     | Quality Secured Preforming                                 | 225 |
| 5.1   | Macro Preform Quality                                      | 225 |
| 5.2   | Micro Preform Quality                                      | 225 |
| 5.3   | Fiber Disturbance at Seams                                 | 226 |
| 6     | Liquid Composite Molding Process<br>for Net-Shape Preforms | 227 |
| 6.1   | Preform LCM Process Chain                                  | 227 |
| 6.2   | Thermal Behavior of Seam in FRPC                           | 228 |
| 7     | Quality Management   | 228 |
| 8     | Conclusions  | 231 |
| 9     | Acknowledgements   | 231 |
| 10    | References   | 231 |

## **Chapter 13 Deconsolidation and Reconsolidation of Thermoplastic Composites During Processing 233**

|     |  |     |
|-----|--|-----|
| 1   | Introduction                                     | 233 |
| 2   | Experimental Observations                        | 235 |
| 2.1 | Void Growth                                      | 235 |
| 2.2 | Migration of Voids                               | 236 |
| 2.3 | Squeezed Flow of Resin During Reconsolidation    | 237 |
| 3   | Mechanistic Model of the Void Growth             | 238 |
| 3.1 | Discussion of the Mechanism                      | 238 |
| 3.2 | Void-Growth Model                                | 241 |
| 3.3 | Theoretical Predictions                          | 244 |
| 4   | Thermal/Mechanistic Models of Migration of Voids | 246 |
| 4.1 | Discussion of Mechanisms                         | 246 |
| 4.2 | Thermal Analysis                                 | 246 |
| 4.3 | Void Closure                                     | 249 |
| 4.4 | Squeezed Creep Flow of Resin                     | 251 |
| 5   | Conclusions                                      | 253 |
| 6   | Acknowledgement                                  | 253 |
| 7   | References                                       | 253 |

## **Chapter 14 Long Fiber-Reinforced Thermoplastic Composites in Automotive Applications 255**

|   |   |     |
|---|---|-----|
| 1 | Introduction  | 255 |
| 2 | Long Glass Fiber-Reinforced Polypropylene<br>with Mineral Fillers     | 257 |
| 3 | Long Fiber-Reinforced Polyamide 66 with Minimized<br>Water Absorption | 259 |

|   |  |     |
|---|--|-----|
| 4 | Long Fiber-Reinforced Thermoplastic Styrene Resins for Car Interior Applications | 259 |
| 5 | Conclusions  | 261 |
| 6 | References   | 261 |

## **Part IV Mechanical Performance of Macrocomposites 263**

### **Chapter 15 Deformation Mechanisms in Knitted Fabric Composites 265**

|       |  |     |
|-------|--|-----|
| 1     | Introduction   | 265 |
| 2     | Knitted Fabrics  | 267 |
| 3     | Material Characterization and Deformation Behavior         | 268 |
| 3.1   | Raw Materials  | 268 |
| 3.2   | Material Characterization                                  | 268 |
| 3.2.1 | Tensile Testing  | 268 |
| 3.2.2 | V-Bending  | 268 |
| 3.2.3 | Dome Forming   | 269 |
| 3.2.4 | Cup Forming  | 269 |
| 4     | Experimental Results and Grid Strain Analysis              | 269 |
| 4.1   | Tensile Testing  | 269 |
| 4.2   | V-bending  | 270 |
| 4.3   | Dome Forming   | 271 |
| 4.4   | Cup Forming  | 273 |
| 5     | Textile Composite Deformation Mechanisms                   | 274 |
| 5.1   | Prepreg Flow Mechanisms                                    | 274 |
| 5.2   | Macro-Level Fabric Deformation Modes                       | 274 |
| 5.3   | Micro-Level Fabric Deformation Modes                       | 275 |
| 5.4   | Textile Fabric Force-Displacement Curve                    | 276 |
| 5.5   | Experimental Force-Displacement Curves                     | 278 |
| 6     | Modeling the Manufacture of the Reinforcement Architecture | 278 |
| 6.1   | Model Set-Up   | 279 |
| 6.2   | Model Input: Knitting Machine Parameters                   | 280 |
| 6.3   | Model Input: Material Property Parameters                  | 280 |
| 6.4   | Model Input: Non-Physical Parameters                       | 282 |
| 6.5   | Simulating the Mechanics of the Knitting Process           | 283 |
| 7     | Concluding Remarks   | 284 |
| 8     | Acknowledgements   | 286 |
| 9     | References   | 286 |

### **Chapter 16 Impact Damage in Composite Laminates 289**

|   |  |     |
|---|--|-----|
| 1 | Introduction   | 289 |
| 2 | Deformation and Energy Release Rate of Axisymmetric Plates with Multiple Delaminations | 291 |



|     |   |     |
|-----|---|-----|
| 2.1 | Axisymmetric Plate with Multiple Delaminations of the Same Size | 291 |
| 2.2 | A Delamination is Larger or Smaller than the Rest               | 293 |
| 2.3 | Effect of geometrical nonlinearity                              | 295 |
| 2.4 | Finite Element Analysis   | 296 |
| 2.5 | Some Derived Relationships                                      | 297 |
| 3   | Effect of the Stacking Sequence                                 | 300 |
| 4   | Simulation of Delamination Growth in Composite Laminates        | 304 |
| 5   | Conclusion  | 305 |
| 6   | References  | 306 |

## **Chapter 17 Discontinuous Basalt Fiber-Reinforced Hybrid Composites 309**

|     |  |     |
|-----|--|-----|
| 1   | Introduction   | 309 |
| 2   | Basalt Fibers  | 310 |
| 2.1 | Characteristics, Applications                                    | 310 |
| 2.2 | Production and Properties of Melt-Blown Basalt Fibers            | 313 |
| 3   | Hybrid Composites  | 314 |
| 3.1 | Concept and Realization  | 314 |
| 3.2 | Property Prediction  | 316 |
| 3.3 | Applications   | 317 |
| 4   | Thermoplastic Hybrid Composites                                  | 317 |
| 4.1 | Polypropylene with Hybrid Reinforcement Containing Basalt Fibers | 317 |
| 4.2 | Basalt Fiber-Reinforced Polymer Blends                           | 319 |
| 5   | Thermoset Hybrid Composites                                      | 321 |
| 5.1 | Basalt Fiber Mat-Reinforced Hybrid Thermosets                    | 321 |
| 5.2 | Hybrid Fiber Mat-Reinforced Hybrid Thermosets                    | 323 |
| 6   | Conclusions and Outlook  | 324 |
| 7   | Acknowledgement  | 325 |
| 8   | References   | 325 |

## **Chapter 18 Accelerated Testing Methodology for Polymer Composite Durability 329**

|     |  |     |
|-----|--|-----|
| 1   | Introduction   | 329 |
| 2   | Prediction Procedure of Fatigue Strength             | 330 |
| 3   | Some Experimental Details and Relationships Obtained | 330 |
| 3.1 | Experimental Procedure                               | 330 |
| 3.2 | Failure Mechanism                                    | 331 |
| 3.3 | Master Curve for the CSR Strength                    | 333 |
| 3.4 | Master Curve for Creep Strength                      | 334 |

|   |            |
|---|------------|
| 3.5 Master Curve for the Fatigue Strength<br>at Zero Stress Ratio | 335        |
| 3.6 Prediction of Fatigue Strength<br>for Arbitrary Stress Ratios | 337        |
| 4 Applicability of the Prediction Method                          | 338        |
| 5 Conclusion  | 339        |
| 6 References  | 340        |
| <b>Contributing Authors</b>                                       | <b>343</b> |
| <b>List of Acknowledgements</b>                                   | <b>357</b> |
| <b>Author Index</b>   | <b>361</b> |
| <b>Subject Index</b>  | <b>363</b> |